



SECURE | CERTIFIED | CONNECTED



SECURE PERIPHERAL SWITCHING SOLUTIONS



Most Belkin Secure Switching products are certified by NIAP to the latest Common Criteria Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.

KVM ACCESSORIES

F1D006



F1D008



Belkin Secure KVM Mounting Brackets

MODEL NUMBER	DESCRIPTION
F1D006	Desk mount for F1DN10xB/C/P
F1D008	Desk mount for F1DN104E/F/Q/W

Belkin Secure Desktop Controller Unit (DCU)

F1DN003R

MODEL NUMBER	DESCRIPTION
F1DN002R	4 Button DCU for 4 port Belkin Secure KVM Switches, with LCD Display
F1DN003R	3 Button DCU for 4-16 port Belkin Secure KVM Switches, with LCD Display



Belkin Secure CAC Reader

MODEL NUMBER	DESCRIPTION
F1DN005U	USB Smart Card/CAC Reader



F1DN005U

Belkin Smart Cables

F1D9008b06



SKVM PC CONNECTION COMBO CABLES	SINGLE OUTPUT PC		
	DESCRIPTION	RECOMMENDED USAGE	
HDMI to HDMI	F1DN1CCBL-HH-6	HDMI to HDMI High Retention KVM Combo Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3
	F1DN1CCBL-HH-10	HDMI to HDMI High Retention KVM Combo Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3
DVI DL to HDMI	F1DN1CCBL-DH-6	DVI-D to HDMI High Retention KVM Combo Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3
	F1DN1CCBL-DH-10	DVI-D to HDMI High Retention KVM Combo Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3
USB-C to DP	F1DN1CCBL-CP-6	USB-C to DP KVM Active Combo Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN104P-3, F1DN104Q-3 (Single DP Connection)
	F1DN1CCBL-CP-10	USB-C to DP KVM Active Combo Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN104P-3, F1DN104Q-3 (Single DP Connection)
mDP to DP	F1DN1CCBL-MP-6	MiniDP to DP KVM Combo Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN104P-3, F1DN104Q-3 (Single DP Connection)
	F1DN1CCBL-MP-10	MiniDP to DP KVM Combo Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN104P-3, F1DN104Q-3 (Single DP Connection)
DP to DP	F1D9019b06	DP to DP KVM Combo Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN104P-3, F1DN104Q-3 (Single DP Connection)
	F1D9019b10	DP to DP KVM Combo Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN104P-3, F1DN104Q-3 (Single DP Connection)
DVI to DVI	F1D9012b06	DVI-D to DVI-D KVM Combo Cable, 6'	F1DN104B-3, F1DN104C-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN116C-3, F1DN204M-3
	F1D9012b10	DVI-D to DVI-D KVM Combo Cable, 10'	F1DN104B-3, F1DN104C-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN116C-3, F1DN204M-3
VGA to DVI-A	F1D9015b06	VGA to DVI-A KVM Combo Cable, 6'	F1DN104B-3, F1DN104C-3, F1DN104E-3, F1DN104F-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN204M-3
	F1D9015b10	VGA to DVI-A KVM Combo Cable, 10'	F1DN104B-3, F1DN104C-3, F1DN104E-3, F1DN104F-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN204M-3
VGA to DVI-D	F1D9009b06	VGA to DVI-D KVM Active Combo Cable, 6'	F1DN104B-3, F1DN104C-3, F1DN104E-3, F1DN104F-3, F1DN104Q-3, F1DN108C-3, F1DN108F-3, F1DN116C-3
DP to DVI-D	F1D9017b06	DP to DVI-D Active Combo Cable, 10'	F1DN104B-3, F1DN104C-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN116C-3, F1DN204M-3
	F1D9017b10	DP to DVI-D Active Combo Cable, 6'	F1DN104B-3, F1DN104C-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN116C-3, F1DN204M-3

SKVM PC CONNECTION COMBO CABLES	DUAL OUTPUT PC	DESCRIPTION	RECOMMENDED USAGE
HDMI to HDMI	F1DN2CCBL-HH-6	Dual-Head HDMI to HDMI High Retention KVM Combo Cable, 6'	F1DN202KVM-UN-3, F1DN204KVM-UN-3
	F1DN2CCBL-HH-10	Dual-Head HDMI to HDMI KVM Combo Cable, 10'	F1DN202KVM-UN-3, F1DN204KVM-UN-3
DVI to HDMI	F1DN2CCBL-DH-6	Dual-Head DVI-D to HDMI KVM Combo Cable, 6'	F1DN202KVM-UN-3, F1DN204KVM-UN-3
	F1DN2CCBL-DH-10	Dual-Head DVI-D to HDMI KVM Combo Cable, 10'	F1DN202KVM-UN-3, F1DN204KVM-UN-3
DVI to HDMI and DP to DP	F1DN2CC-DHPP-6	Dual-Head DVI-D to HDMI and DP to DP KVM Combo Cable, 6'	F1DN202KVM-UN-3, F1DN204KVM-UN-3
	F1DN2CC-DHPP-10	Dual-Head DVI-D to HDMI and DP to DP KVM Combo Cable, 10'	F1DN202KVM-UN-3, F1DN204KVM-UN-3
USB-C to DP	F1DN2CCBL-CP-6	Dual-Head USB-C to DP Active KVM Combo Cable, 6'	F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104Q-3 (Dual DP Connection), F1DN104W-3
	F1DN2CCBL-CP-10	Dual-Head USB-C to DP Active KVM Combo Cable, 10'	F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104Q-3 (Dual DP Connection), F1DN104W-4
mDP to DP	F1DN2CCBL-MP-6	Dual-Head MiniDP to DP KVM Combo Cable, 6'	F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104Q-3 (Dual DP Connection), F1DN104W-3
	F1DN2CCBL-MP-10	Dual-Head MiniDP to DP KVM Combo Cable, 10'	F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104Q-3 (Dual DP Connection), F1DN104W-3
DP to DP	F1D9020b06	Dual-Head DP to DP KVM Combo Cable, 6'	F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104Q-3 (Dual DP Connection), F1DN104W-3
	F1D9020b10	Dual-Head DP to DP KVM Combo Cable, 10'	F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104Q-3 (Dual DP Connection), F1DN104W-3
DVI to DVI	F1D9014b06	Dual-Head DVI-D to DVI-D KVM Combo Cable, 6'	F1DN104E-3, F1DN104F-3, F1DN108F-3
	F1D9014b10	Dual-Head DVI-D to DVI-D KVM Combo Cable, 10'	F1DN104E-3, F1DN104F-3, F1DN108F-3

SKVM MONITOR OR VIDEO ONLY CABLES

DP to DP	F1DN1VCBL-PP-6	DP to DP Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104P-3, F1DN104W-3, F1DN104Q-3
	F1DN1VCBL-PP-10	DP to DP Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104P-3, F1DN104W-3, F1DN104Q-4
HDMI to HDMI	F1DN1VCBL-HH-6	HDMI to HDMI Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104P-3, F1DN104W-3, F1DN104Q-3 (HDMI Output)
	F1DN1VCBL-HH-10	HDMI to HDMI Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104P-3, F1DN104W-3, F1DN104Q-3 (HDMI Output)
	F8V3311b025	HDMI to HDMI Cable, 25'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104P-3, F1DN104W-3, F1DN104Q-3 (HDMI Output)
HDMI to DVI DL	F1DN1VCBL-DH-6	HDMI to DVI-DL Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104P-3, F1DN104W-3, F1DN104Q-3 (DVI Input/Output)
	F1DN1VCBL-DH-10	HDMI to DVI-DL Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104P-3, F1DN104W-3, F1DN104Q-3 (DVI Input/Output)
DP to mDP	F1DN1VCBL-MP-6	DP to MiniDP Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3
	F1DN1VCBL-MP-10	DP to MiniDP Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3
DVI-D to DVI-D	F2E7171-03-DV	DVI-D Dual-Link Cable, 3'	F1DN104B-3, F1DN104C-3, F1DN104E-3, F1DN104F-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN102F-3, F1DN204M-3
	F2E7171-10-DV	DVI-D Dual-Link Cable, 10'	F1DN104B-3, F1DN104C-3, F1DN104E-3, F1DN104F-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN102F-3, F1DN204M-3

OTHER CABLES/ADAPTERS

CAC	F1D9013b06	USB A to USB B Cable for CAC Reader, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104C-3, F1DN104F-3, F1DN104Q-3, F1DN104P-3, F1DN104W-3, F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN204M-3
	F1D9013b10	USB A to USB B Cable for CAC Reader, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104C-3, F1DN104F-3, F1DN104Q-3, F1DN104P-3, F1DN104W-3, F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN204M-3
USB/Audio	F1D9022b06	USB Keyboard/Mouse/Audio Combo Cable, 6'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104C-3, F1DN104F-3, F1DN104Q-3, F1DN104P-3, F1DN104W-3, F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN204M-3
	F1D9022b10	USB Keyboard/Mouse/Audio Combo Cable, 10'	F1DN102KVM-UN-3, F1DN104KVM-UN-3, F1DN202KVM-UN-3, F1DN204KVM-UN-3, F1DN104C-3, F1DN104F-3, F1DN104Q-3, F1DN104P-3, F1DN104W-3, F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN204M-3
DCU	F1D9026-50	50' RJ25 Extension for DCU	F1DN002R, F1DN003R
DVI-A to VGA	F2E4161	DVI-A to VGA Bidirectional Adapter	F1DN104B-3, F1DN104C-3, F1DN104E-3, F1DN104F-3, F1DN104Q-3 (DVI connection), F1DN108C-3, F1DN108F-3, F1DN116C-3, F1DN204M-3

PRODUCT COMPARISON

	BELKIN SECURE UNIVERSAL KVM				BELKIN SECURE 2-PORT FLIP KVM			BELKIN SECURE DVI-I KVM				BELKIN SECURE DISPLAYPORT KVM			BELKIN SECURE 8/16 PORT KVM			BELKIN SECURE KM		
Product Photo																				
Part Number	F1DN102KVM-UN-3	F1DN202KVM-UN-3	F1DN104KVM-UN-3	F1DN204KVM-UN-3	F1DN102N-3	F1DN102F-3	F1DN102V-3	F1DN104B-3	F1DN104C-3	F1DN104E-3	F1DN104F-3	F1DN104P-3	F1DN104W-3	F1DN104Q-3	F1DN108C-3	F1DN108F-3	F1DN116C-3	F1DN102K-3	F1DN104K-3	F1DN108K-3
Product Description	Secure Universal 2 Port Single Monitor DP/HDMI to DP/HDMI SKVM w/CAC	Secure Universal 2 Port Dual Monitor DP/HDMI to DP/HDMI SKVM w/CAC	Secure Universal 4 Port Single Monitor DP/HDMI to DP/HDMI SKVM w/CAC	Secure Universal 4 Port Dual Monitor DP/HDMI to DP/HDMI SKVM w/CAC	Secure Flip 2-Port Ultra High Def KVM with Audio and Remote Controller	Secure Flip 2-Port DVI-D KVM with Audio and Remote Controller	Secure Flip 2-Port VGA KVM with Audio and Remote Controller	Secure DVI-I KVM Switch; 4-Port	Secure DVI-I KVM Switch; 4-Port with CAC	Secure Dual-Head DVI-I KVM Switch; 4-Port	Secure Dual-Head DVI-I KVM Switch; 4-Port with CAC	Secure Ultra High Def KVM Switch; 4-Port with CAC	Secure DisplayPort Dual-Head KVM Switch; 4-Port with CAC	Secure DisplayPort/DVI Quad-Head KVM Switch; 4-Port with CAC	Secure DVI-I KVM Switch; 8-Port with CAC	Secure Dual-Head DVI-I KVM Switch; 8-Port with CAC	Secure DVI-I KVM Switch; 16-Port with CAC	Secure Flip 2-Port Keyboard/Mouse Switch	Secure 4-Port Keyboard/Mouse Switch	Secure 8-Port Keyboard/Mouse Switch
No. of Computers	2	2	4	4	2	2	2	4	4	4	4	4	4	4	8	8	16	2	4	8
No. of Displays	1	2	1	2	1	1	1	1	1	2	2	1	2	4 (3 x DisplayPort & 1 x DVI)	1	2	1	N/A	Up to 16	Up to 32
Console Ports	USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard)				USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard)			USB Type-A female connector or PS/2 Mini-DIN 6 pin female connector (1 designated mouse port and 1 designated keyboard port)				USB Type-A female connector or PS/2 Mini-DIN 6-pin female connector (1 designated port for mouse and 1 designated port for keyboard)			USB Type-A female connector or PS/2 Mini-DIN 6-pin female connector (1 designated port for mouse and 1 designated port for keyboard)					
Max Resolutions Supported	3840x2160 pixels (UHD 4K) @60Hz				3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz			3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz				3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz			3840x2160 pixels (UHD 4K) @30Hz, 2560x1600 pixels @60Hz					
Console Mouse and Keyboard Ports	USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard)				USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard)			USB Type-A female connector or PS/2 Mini-DIN 6 pin female connector (1 designated mouse port and 1 designated keyboard port)				USB Type-A female connector or PS/2 Mini-DIN 6-pin female connector (1 designated port for mouse and 1 designated port for keyboard)			USB Type-A female connector or PS/2 Mini-DIN 6-pin female connector (1 designated port for mouse and 1 designated port for keyboard)					
Console Display Ports	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a	DisplayPort 1.1/1.2	DVI-D, Single-link	VGA	DVI-I Dual-link	DVI-I Dual-link	2 x DVI-I Dual-link	2 x DVI-I Dual-link	1 x HDMI 1.4	2 x HDMI 1.4	3 x HDMI 1.4 & 1 x DVI-I Dual-link	DVI-I Dual-link	2 x DVI-I Dual-link	DVI-I Dual-link	N/A	N/A	N/A
Console Audio Jack	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)
Remote Control	DCU	DCU	DCU	DCU	Button RC	Button RC	Button RC	DCU	DCU	DCU	DCU	DCU	DCU	DCU	DCU	DCU	DCU	N/A	DCU	DCU
Computer Ports	USB Type B				USB Type A			USB Type B				USB Type B			USB Type B			USB Type A		
Computer Keyboard/Mouse Ports	USB Type B				USB Type A			USB Type B				USB Type B			USB Type B			USB Type A		
Computer CAC Ports	USB Type B				N/A			N/A				N/A			N/A			N/A		
Computer Audio Jack	1/8" (3.5mm male)	1/8" (3.5mm male)	1/8" (3.5mm male)	1/8" (3.5mm male)	1/8" (3.5mm male)	1/8" (3.5mm male)	1/8" (3.5mm male)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm female)	1/8" (3.5mm male)	1/8" (3.5mm female)	1/8" (3.5mm female)
Console CAC and Biometrics	USB Type A				N/A			N/A				N/A			N/A			N/A		
Computer Display Ports	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a	1 Combo HDMI 2.0/DP 1.2a	2 Combo HDMI 2.0/DP 1.2a	DisplayPort	DVI-D Single-link	VGA D-Sub 15 HD female	DVI Dual-link female	DVI Dual-link female	2 x DVI-I Dual-link female	2 x DVI-I Dual-link female	1 x DisplayPort 1.1/1.2	2 x DisplayPort 1.1/1.2	3 x DisplayPort 1.1/1.2 & 1 x DVI-I Dual-link	DVI-I	2 x DVI-I	DVI-I	N/A	N/A	N/A
Physical	12.5 (W) x 6.2 (D) x 1.9 (H) inch				4.3 (W) x 3 (D) x 1 (H) inch			12.5 (W) x 6.2 (D) x 1.9 (H) inch				21.5 (W) x 6.2 (D) x 1.9 (H) inch			17.3 (W) x 7.8 (D) x 1.7 (H) inch			4.3 (W) x 3 (D) x 1 (H) inch		
Dimensions	371.5 (W) x 157.5 (D) x 48.3 (H) mm				109.2 (W) x 76.2 (D) x 25.4 (H) mm			371.5 (W) x 157.5 (D) x 48.3 (H) mm				317.5 (W) x 157.5 (D) x 63.5 (H) mm			432.5 (W) x 42.5 (D) x 195 (H) mm			109.2 (W) x 76.2 (D) x 25.4 (H) mm		
Weight	3.9 lbs. / 1.8 kg.				1.6 lbs. / 0.73 kg.			3.9 lbs. / 1.8 kg.				5.1 lbs. / 2.3 kg.			10.0 lbs. / 4.5 kg.			1.2 lbs. / 0.54 kg.		
Power	12V DC, 1.5A				12V, 1A DC			12V DC, 1.5A				12V DC, 1.5A			100-240VAC, 0.9A Max, 50/60Hz			12V, 1A DC		
Power Requirements	12V DC, 1.5A				12V, 1A DC			12V DC, 1.5A				12V DC, 1.5A			100-240VAC, 0.9A Max, 50/60Hz			12V DC 1.5A		
AC Input	100 to 240VAC with worldwide interchangeable mains connector				100-240VAC			100 to 240VAC				100 to 240VAC			100 to 240VAC			100-240VAC		
Power Type	External				External			External				External			Internal			External		
Environmental & Certification	Certified to NIAP Protection Profile PSS Ver 3.0, which exceeds EAL4. NIAP listing pending.				NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.			NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.				NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.			NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.			NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.		
Operating Temperature	32° to 104° F (0° to 40° C)				32° to 104° F (0° to 40° C)			32° to 104° F (0° to 40° C)				32° to 104° F (0° to 40° C)			32° to 104° F (0° to 40° C)			32° to 104° F (0° to 40° C)		
Storage Temperature	-4° to 140° F (-20° to 60° C)				-4° to 140° F (-20° to 60° C)			-4° to 140° F (-20° to 60° C)				-4° to 140° F (-20° to 60° C)			-4° to 140° F (-20° to 60° C)			-4° to 140° F (-20° to 60° C)		
Humidity	0-80% RH, non-condensing				0-80% RH, non-condensing			0-80% RH, non-condensing				0-80% RH, non-condensing			0-80% RH, non-condensing			0-80% RH, non-condensing		
Security Accreditation	Certified to NIAP Protection Profile PSS Ver 3.0, which exceeds EAL4. NIAP listing pending.				NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.			NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.				NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.			NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.			NIAP certified to latest Protection Profile PSS Ver 3.0, which exceeds EAL4 and PP PSS Ver. 2.1.		
General Information	Designed and supported in California. Assembled in U.S. TAA compliant.				Designed and supported in California. Assembled in U.S. TAA compliant.			Designed and supported in California. Assembled in U.S. TAA compliant.				Designed and supported in California. Assembled in U.S. TAA compliant.			Designed and supported in California. Assembled in U.S. TAA compliant.			Designed and supported in California. Assembled in U.S. TAA compliant.		
Made In	Designed and supported in California. Assembled in U.S. TAA compliant.				Designed and supported in California. Assembled in U.S. TAA compliant.			Designed and supported in California. Assembled in U.S. TAA compliant.				Designed and supported in California. Assembled in U.S. TAA compliant.			Designed and supported in California. Assembled in U.S. TAA compliant.			Designed and supported in California. Assembled in U.S. TAA compliant.		
Product Life-Cycle	5 Years				5 Years			5 Years				5 Years			5 Years			5 Years		
Warranty	3 Years Standard - Optional Extended up to 5 Years				3 Years Standard - Optional Extended up to 5 Years			3 Years Standard - Optional Extended up to 5 Years				3 Years Standard - Optional Extended up to 5 Years			3 Years Standard - Optional Extended up to 5 Years			3 Years Standard - Optional Extended up to 5 Years		
Enclosure	Heavy-duty extruded aluminum enclosure with metal faceplate.				Impact Resistant ABS Plastic			Heavy-duty extruded aluminum enclosure with metal faceplate				Heavy-duty extruded aluminum enclosure with metal faceplate.			Heavy-duty extruded aluminum enclosure with metal faceplate.			Impact Resistant ABS Plastic		

THE CHALLENGE

Exponential increases in cyber-attacks present a constant risk to companies' data, IP, and critical infrastructures; thus highlighting the need to extend network isolation to the desktop.



THE SOLUTION

Belkin offers a wide set of NIAP Protection Profile 3.0 certified products designed to maintain air-gap isolation at the desktop while improving operator efficiency and effectiveness.

THE ULTIMATE SECURITY SOLUTION

All Belkin secure switching products are equipped with a host of security features including:

- Optical data diodes assuring unidirectional data flow.
- No shared resources between physically isolated computers.
- Strong authentication and filtering of connected USB devices.
- Secured EDID communication ensuring protection of connected monitors.

TAMPER PROOF SYSTEM

All Belkin secure switching products are equipped with an end-to-end tamper proof system including:

- Active always-on anti-tamper system disabling product once switch's electronic circuitry is accessed or tampered with.
- A holographic security tamper-evident label on switch enclosure to indicate if product has been opened or compromised.
- Heavy-duty tamper-resistant enclosure with built-in mounting option for simpler desktop deployment.
- Secure "tear-away" packaging for secure delivery of product.

Differences between secure KVM and secure KM switches

Belkin KVMs securely switch control of video, audio, keyboard and mouse between computers. The benefits are many including better space efficiencies, better worker productivity and reduced cost by eliminating extraneous peripherals. Belkin KMs switch only keyboard, mouse and audio while displays are connected directly to their respective computers, enabling full situational awareness across up to 32 monitors. KMs automatically and seamlessly switch channels as operators move the cursor from one monitor to another.

WHO ARE WE?

Belkin, a proven technology leader for more than 30 years, provides high-quality customized solutions that align seamlessly to enhance the technologies that businesses, schools, government agencies and other professional organizations depend on for their growth and success. Belkin is dedicated to developing innovative solutions to address the challenges of the modern workplace.

Belkin International, Inc.

12045 E. Waterfront Drive, Playa Vista, CA 90094
(310) 751-5569

www.belkin.com/cybersecurity

