



Ideal Solutions for Rapid Deployment and Travel.

Remote Work Solutions.

Delivering cybersecurity solutions wherever you go.

The Modular Secure KVM or KM form factor boasts a 94% reduction in size and weight compared to traditional Secure KVMs or KMs. This makes it an ideal solution for remote work or travel, particularly when operating off a VPN. With its compact design, the Modular Secure KVM or KM can securely consolidate the desktop with minimal transport bulk. In addition, its small form factor allows for efficient organization-wide equipment transport and deployment, resulting in reduced storage space requirements and lower transportation costs.



	Modular Secure KVM	Modular Secure KM
Part Numbers	FIDN102MOD-BA-4, -PP-4, -HH-4, -DD-4 FIDN202MOD-BA-4, -PP-4, -HH-4, -DD-4 FIDN104MOD-BA-4, -PP-4, -HH-4, -DD-4 FIDN204MOD-BA-4, -PP-4, -HH-4, -DD-4 FIDN108MOD-BA-4 FIDN208MOD-BA-4	FIDN002MOD-KM-4 FIDN004MOD-KM-4
No. of Computers	2, 4, 8	2, 4
No. of Displays	1, 2	8, 16
Video Channel Switching	Protected	N/A
Video Capability	Universal	N/A
Supports	DisplayPort™, mDP, DPMST, HDMI®, DVI-D, VGA and USB-C® via Unique Cabling	USB-A
Console Ports		
Console Mouse and Keyboard Ports	USB Type-A female connector (1 designated port for mouse and 1 designated port for keyboard) with status indicator lights	
Console Remote Control Port	USB Mini (female)	
Console Video Port	DP, HDMI, DVI-D, VGA	None
Integrated Console Cable	1 x 6 ft. (1.8m) Single or dual-monitor integrated video cable	N/A
Max Resolution Supported	3840 x 2160 pixels (UHD 4K) @ 30Hz	N/A
Computer Ports		
Computer Keyboard/Mouse Port	USB Type-A	
Computer Video Port	DisplayPort™, mDP, DPMST, HDMI®, DVI-D, VGA and USB-C®	None
Integrated Computer Cable	2 x 6 ft. (1.8m) integrated cables for video and USB 4 x 6 ft. (1.8m) integrated cables for video and USB	2 x 6 ft. (1.8m) integrated cables for USB 4 x 6 ft. (1.8m) integrated cables for USB
Power		
Power Requirements	12V, 2.5A DC	
AC Input	100-240VAC	
Power Type	External with WW mains connectors	
Physical		
Dimensions	3.5 (W) x 0.6 (H) x 7.5 (L) in. / 90 (W) x 15 (H) x 190 (L) mm 2.7 (W) x 0.68 (H) x 12.89 (L) in. / 69 (W) x 17 (H) x 327 (L) mm	3.5 (W) x 7.5 (D) x .6 (H) in. / 90 (W) x 190 (D) x 15 (H) mm
Smallest Form Factor (SFF)	Yes	
Certification		
Security Accreditation	NIAP Protection Profile PSD Ver. 4.0, Audio Input v 1.0, Keyboard/Mouse v 1.0, Video/Display v 1.0 TEMPEST variants available via an SDIP-55 NATO accredited TEMPEST test facility.	NIAP Protection Profile PSD Ver. 4.0, Keyboard/Mouse v 1.0, TEMPEST variants available via an SDIP-55 NATO accredited TEMPEST test facility.
Regulatory Compliance	FCC Class A, CE, UL, ICES, RCM, RoHS, UKCA	
General Information		
Made In	Designed in California. Assembled in US with US-based technical support (TAA compliant).	
Warranty	3 years standard (upgradeable to 4 or 5 years)	
Technical Support	US-based free technical support	
Future Proof	As PC and monitor ports upgrade, the SKVM/SKM can accommodate these changes with appropriate connection cable, ensuring high ROI from infrastructure investments	
Optional Mounting Hardware	Supports VESA, Cubicle, and under-the-desk mounting	
Remote Control	Included	

Learn More About our Modular Series



For additional information, please contact your Belkin representative:

[Belkin.com/cybersecurity](https://www.belkin.com/cybersecurity) | [Belkinchat.com](https://www.belkinchat.com)