



Be Ready For Today™

Connect 12-Port Dual Display USB-C® Dock

Professionals looking to expand setups and optimize efficiency can increase their laptop's ports up to a dozen and connect dual displays plus peripherals. This dock is compatible with HDMI® or DisplayPort technology, and one integrated USB-C cable powers and extends workstations. It supplies up to 140W Power Delivery to your host device, data transfer speeds up to 10Gbps, and up to 2.5Gb Ethernet.



Extend or mirror your laptop displays up to dual monitors with HDMI or DisplayPort resolutions up to 4K@60Hz



Expand your laptop's ports to 12 additional connections for data, charge, media and hardwired Ethernet

140W

Charge your host device and other devices simultaneously with up to 140W Power Delivery



Transfer data at speeds up to 10Gbps with USB-C 3.2 Gen 2 – twice as fast as USB 3.0



Rely on a fast, dependable hardwired network 2.5Gb Ethernet connection



Enjoy compatibility with Belkin Dock Utility Software



Be Ready For Today™

Technical Specs

- Ports
- Front:
- 2x USB-A 3.0 (5Gbps)
 - 1x USB-A 3.0 (7.5W, 5Gbps)
 - 1x USB-C 3.2 (15W, 10Gbps)
 - 1x USB-C 3.2 (7.5W, 10Gbps)
 - 3.5mm audio combo port
- Back:
- 1x USB-A 3.0 (5Gbps)
 - 2.5Gb Ethernet
 - 2x HDMI 2.0 (4K@60Hz)
 - 1x DisplayPort (4K@60Hz)
 - USB-C 3.1 (140W PD, 10Gbps)
 - PSU 180W
- Kensington lock
 - VESA mount compatible
 - Belkin Dock Utility Software compatible



Display Setup	HDMI #1 or DP	HDMI #2
Single Monitor	4K@60Hz	4K@60Hz
Dual Monitor	4K@60Hz	4K@60Hz

Notes: Actual output varies based on host device specifications.*
Windows and Chrome OS support MST (Multi-Stream Transport) to offer extended displays. macOS only supports SST (Single-Stream Transport) to mirror displays.

- 1) Laptops with DP 1.4: single display up to 4K@60Hz, dual displays up to 4K@60Hz.
2) Laptops with DP 1.2: single display up to 4K@30Hz, dual displays up to 1080p@60Hz.

macOS supports SST (Single-Stream Transport) only to offer mirror displays.
macOS can support up to 4K@30Hz for dual mirrored displays.

Compatibility

Compatible with devices that have a video-enabled USB-C port such as laptops, tablets, smartphones and Thunderbolt™ 5, Thunderbolt™ 4, Thunderbolt™ 3 ports. Supports Windows, Mac and Chrome OS.

Physical Characteristics

- Product Dimensions
- 5.53 in./140.5mm (L) x 4.14 in./105.16mm (W) x 1.59 in./40.39mm (H)
 - Weight: 1.11 lb/503.6g
 - Included USB-C cable length: 3.3 ft./1m
 - PSU cable length: 3.3 ft./1m
- Packaging Dimensions
- 6.6 in./168.28mm (L) x 5.3 in./133.35mm (W) x 3.9 in./98.43mm (H)

Warranty

Protected by a 3-year Belkin warranty

Package Includes

- Connect 12-Port Dual Display USB-C Dock
- 3.3 ft./1m USB-C cable
- 180W PSU and 3.3 ft./1m power cord

The Belkin Difference

Trusted by 1 billion+[†]
Pioneer in innovation and technology for over 40 years
Extensive testing procedures guarantee quality and durability

Part numbers by region

AMER	INC034t1BK, INC034bkBK
EMEA	INC034kqBK

*Full functionality dependent on host computer.
[†]Belkin has sold over 1 billion products globally since 2000.

© 2026 Belkin International, Inc. All rights reserved. All trade names are registered trademarks of respective manufacturers listed. USB-C is a registered trademark of USB Implementers Forum. Thunderbolt is a trademark of Intel Corporation in the U.S. and/or other countries. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. PR1787300

Belkin International Inc.
El Segundo, CA 90245, USA
Belkin Ltd. Northants, United Kingdom
Belkin Ltd. Tuggerah, Australia